

# 190501 Velomitor\* CT Velocity Transducer

## Product Datasheet

Bently Nevada\* Asset Condition Monitoring

---



### Description

The Velomitor CT Velocity Transducer is a low-frequency version of our standard Velomitor Piezo-velocity Sensor. Its design specifically measures casing vibration velocity on cooling tower and air-cooled heat-exchanger fan assemblies that operate at or above 90 rpm (100 to 300 rpm typical). The Velomitor CT Transducer can measure vibration amplitudes at these frequencies as well as the vibration frequencies generated by the fan motor and speed reducer.

### Application Advisory

If you are making housing measurements for overall protection of the machine, consider the usefulness of the measurement for each application. Most common machine malfunctions (imbalance, misalignment, etc.) originate at the rotor and cause an increase (or at least a change) in rotor vibration.

For any housing measurement alone to be effective for overall machine protection, a significant amount of rotor vibration must be faithfully transmitted to the bearing housing or machine casing, or more specifically, to the mounting location of the transducer.

Exercise care when physically installing the transducer. Improper installation can result in the degradation of transducer amplitude and frequency response, and the generation of signals that do not represent actual machine vibration.

Upon request, we can provide engineering services to determine the appropriateness of housing measurements for the machine in question and to provide installation assistance as needed.



---

## Specifications

Parameters are specified from +20 °C to +30 °C (+68 °F to +86 °F) and 100 Hz unless otherwise indicated.

**Note:** Operation outside the specified limits will result in false readings or loss of machine monitoring.

---

### Electrical

#### Sensitivity

3.94 mV/mm/s (100 mV/in/s)  $\pm$ 5%.

#### Frequency Response

3.0 Hz to 900 Hz (180 to 54,000 cpm)  $\pm$ 1.0 dB

1.5 Hz to 1.0 kHz (90 to 60,000 cpm)  $\pm$ 3.0 dB

#### Temperature Sensitivity

-8% to +5% typical over the operating temperature range.

#### Velocity Range

63.5 mm/s pk (2.5 in/s pk) (see Figure 4 and Figure 5). Vibration components in excess of 10g pk above 1 kHz can significantly reduce this range.

#### Transverse Response

Less than 5% of the axial sensitivity.

#### Amplitude Linearity

$\pm$ 2% to 63.5 mm/s pk (2.5 in/s pk)

#### Mounted Resonant Frequency

9 kHz, minimum (stud mounted, except quick disconnect)

#### Output Bias Voltage

10.1 Vdc  $\pm$  1.0 Vdc, Pin A referenced to Pin B

#### Dynamic Output Impedance

<400  $\Omega$  typical

#### Broadband Noise Floor (1.5 Hz to 1 kHz)

0.229 mm/s (0.009 in/s) pk. See Figure 6 for typical noise floor.

#### Base Strain Sensitivity

0.43 mm/s/ $\mu$ strain (0.017 in/s/ $\mu$ strain).

#### Grounding

Internal electronics are isolated from case.

#### Maximum Cable Length

305 metres (1,000 feet) of cable (part number 02173006) with no degradation of signal. Note: Maximum continuous length of cable available is 300 feet. If longer lengths are required they must be spliced or have a connector installed on them.

---

### Environmental Limits

#### Operating Temperature

-40 °C to +85 °C (-40 °F to +185 °F).

#### Storage Temperature

-40 °C to +100 °C (-40 °F to +212 °F).

#### Shock Limit

5000 g pk, maximum.

#### Humidity Limit

100% condensing, non-submerged.

#### Magnetic Field Susceptibility

<0.0068 mm/s/gauss (0.268 mil/s/gauss) @ 50 gauss, 50-60Hz

---

## Mechanical

### Weight

<297 g (10.5 oz.), typical.

### Mounting Surface

33 mm diameter (1.3 in diameter).

### Height

82 mm (3.2 in).

### Case Material

316L stainless steel

### Connector

2-pin 316L stainless steel MIL-C-5015, top.

### Mounting Torque

4.5 N-m ± 0.6 N-m (40 in-lbf ± 5 in-lbf).

### Polarity

Pin A goes positive with respect to Pin B when velocity is from base to top of the transducer.

### Mounting Angle

Any orientation.

---

## Compliance and Certifications

### Electromagnetic Compatibility

#### Standards

EN 61326-1 Immunity for Industrial Environments

#### European Community Directives

EMC Directive 2014/30/EU

---

## Hazardous Area Approvals

For the detailed listing of country and product specific approvals, refer to the **Approvals Quick Reference Guide**, document 108M1756, at [www.GEmeasurement.com](http://www.GEmeasurement.com).

## CSA/NRTL/C (Agency Approval Options 01 through 04)

### Intrinsically Safe

Ex ia IIC T4  
Class I, Division 1, Groups A,B, C and D  
Class II, Groups E, F and G  
Class III

AEx ia IIC T4  
Class I, Division 1, Groups A, B, C and D  
Class II, Groups E, F and G  
Class III

T4 @ -40 °C ≤ Ta ≤ +100 °C  
(-40 °F ≤ Ta ≤ +212 °F)  
per drawing 167536

### Intrinsically Safe and Non-Incendive

Ex nL IIC T4  
Class I, Division 2, Groups A, B, C and D

AEx nA T4  
Class I, Division 2, Groups A, B, C and D

T4 @ -40 °C ≤ Ta ≤ +100 °C  
(-40 °F ≤ Ta ≤ +212 °F)  
per drawing 167536

## ATEX/IECEx (Agency Approval Options 01 through 04)



II 1 G Ex ia IIC T4 Ga  
II 3 G D Ex nA IIC T4 Gc  
Ex tc IIIC T130 °C Dc

T4 @ -55 °C ≤ Ta ≤ +121 °C  
(-67 °F ≤ Ta ≤ +249.8 °F)

---

## Ordering Information

For a detailed listing of country and product specific approvals, refer to the Approvals Quick Reference Guide, document 108M1756, at [www.GEmeasurement.com](http://www.GEmeasurement.com).

---

### Velomitor CT Velocity Transducer

190501-AXX-BXX-CXX

**A:** Mounting Hardware Option

- 00 No stud
- 01 Stud 3/8-in 24 to 3/8-in 24
- 02 Stud 3/8-in 24 to 1/2-in 20
- 03 Adhesive Stud 3/8-in 24
- 04 Stud M6x1 with 3/8-in 24 adapter
- 05 Adhesive Stud M6x1 with 3/8-24 adapter
- 06 Stud 3/8-in 24 to 1/4-in 28
- 07 Plate Stud 3/8-in 24 to 3/8-in 24
- 08 Plate Stud 3/8-in 24 to 1/2-in 20
- 09 Plate Stud 3/8-in 24 to 1/4-in NPT
- 10 Plate Stud M6x1 to M6x1with 3/8-in 24 adapter
- 11 Plate Stud 3/8-in 24 to 1/4-in 28
- 12 Plate Stud 3/8-in 24 to M8x1
- 13 Quick disconnect stud
- 14 Adapter, 3/8-in 24 to 1/4-in 20
- 15 Adapter, 3/8-in 24 to 5/16-in 18
- 16 Adapter, 3/8-in 24 to 3/8-in 24
- 17 Adapter, 3/8-in 24 to 3/8-in 16
- 18 Adapter, 3/8-in 24 to 1/2-in 13
- 19 Adapter, 3/8-in 24 to 1/4-in 18 NPT
- 20 Adapter, 3/8-in 24 to 3/8-in 18 NPT
- 21 Adapter, 3/8-in 24 to 1/2-in 14 NPT
- 22 Adapter, 3/8-in 24 to 3/4-in 14 NPT
- 23 Adapter, 3/8-in 24 to 1.0-in 11.5 NPT
- 24 Adapter, 3/8-in 24 to 1.25-in 11.5 NPT

**B:** Connection Option

- 00 MIL-C-5015 connection interface
- 99 Unit with included 32-foot cable

**C:** Agency Approval Option

- 00 No approvals
- 01 through 04 CSA/NRTL/C (Class I, Division 1), ATEX/IECEX/CSA (Class I, Zone 0/1)

---

### Interconnect Cable

CB2W100-AXXX

Description: Connectors: MIL-C 5015, 2 Socket, Splash Proof, Premium, isolated to blunt cut, Cable: 20 AWG, twisted pair, shielded, yellow Teflon™ jacket. LOCKING RING, ADAPTER SEAL, AND O-RING ARE INCLUDED.

**A:** Length

- 015 15 feet (4.57 metres)
- 032 32 feet (9.75 metres)
- 064 64 feet (19.5 metres)
- 112 112 feet (34.1 metres)
- 125 125 feet (38.1 metres)
- 150 150 feet (45.7 metres)
- 200 200 feet (61.0 metres)
- 250 250 feet (76.2 metres)

---

### Accessories

125389-01

**Velomitor CT Manual**

128608-02

**1/2-in NPT conduit adapter**

04284020-01

**Adhesive mount base kit.** The adhesive mount base kit design is for machines with thin casings that do not permit drilling and tapping a mounting hole. Kit contains material (adhesive and bases) for 2 each 3/8-in 24 UNF adhesive-mount bases. One kit can outfit 2 Velomitor CT Transducers.

---

## Spare Mounting Adapters

All mounting adapters are made from 300 series stainless steel.

---

### Standard Studs

04365657

3/8-in 24 to 3/8-in 24 stud

87910-01

3/8-in 24 to 1/2-in 20 stud

87931-01

M6x1 to M6x1 metric stud  
(requires metric adapter)

87055-01

3/8-in 24 to M6x1 metric  
adapter

89139-01

3/8-in 24 to 1/4-in 28 stud

---

### Hex Plate Studs

107756-01

3/8-in 24 to 3/8-in 24 plate stud

107755-01

3/8-in 24 to 1/2-in 20 plate stud

107754-01

3/8-in 24 to 1/4-in NPT plate  
stud

107757-01

M6x1 to M6x1 plate stud  
(requires metric adapter)

125094-01

3/8-in 24 to M8x1 metric plate  
stud

128038-01

3/8-in 24 to 1/4-in 28 Plate Stud

---

## Quick Disconnect Components

The following three components are included with the quick disconnect mounting option for the Velomitor CT Transducer. The quick disconnect option allows you to remove the transducer without rotating it, allowing you to keep the cable connected to the transducer.

128689-01

**3/8-in 24 to 1¾-in 16 quick disconnect stud base.** Attached to the machine.

43055-01

**1¾-in 16 mounting base nut.** Interface between stud base and transducer piece.

128690-01

**3/8-in 24 quick disconnect stud transducer piece.** Attached to the Velomitor CT Transducer.

---

## Fittings

Conduit fittings allow connection of flexible, metal, liquid-tight conduit or armor to the conduit adapter.

03839201

**1/2-in NPT straight male conduit fitting.** For connecting flexible, liquid-tight conduit to the conduit adapter or a weatherproof enclosure.

03850000

**1/2-in NPT straight, male compression-type fitting.** For connecting Teflon™-coated 3/8-in stainless steel armor to the transducer or a weatherproof enclosure. Fitting will fit Teflon™-coated armor with a maximum outer diameter of 13.8 mm (0.543 in) (including Teflon™ thickness).

---

**Teflon™-Coated Stainless Steel Armor****106924-AXX**

**Note:** This part includes the Teflon™-coated armor but not the cable. You will require 2 1/2-in NPT compression fittings (part number 03850000) to attach the armor to the conduit adapter and terminate it at an enclosure.

**A:** Armor Length Option in Feet

Order in increments of 10 ft (3.0 m)

**Minimum Length:** 10 ft (3.0 m)

**Maximum Length:** 60 ft (18.3 m)

---

**Flexible Metal Conduit****14847-AXX****A:** Flexible Conduit Length Option in Feet

Order in increments of 1 ft (0.3 m)

**Minimum Length:** 01 ft (0.3 m)


**Maximum Length:** 99 ft (30.2 m)

**106769-01**

Terminal housing. Provides a convenient interface between the transducer signal cable and monitor signal cable.

## Dimensional Drawings

**Note:** All dimensions shown are in millimeters (inches) unless noted otherwise.








1. 1/2" NPT x 12.2 DP (1/2" NPT x 0.48 DP)
2. 35.6 (1.40) diameter
3. Cable (not included)
4. Conduit adaptor P/N 128608-02 (not included)
5. 31.8 (1.25) hex flat
6. 31.5 (1.24) diameter
7. 3/8-24 UNF X 8.9 DP (3/8-24 UNF X 0.35 DP)

**Figure 1: Velomitor CT Outline Drawing**


## Spare Mounting Adapters (Illustrations shown are not to scale)

Notes: All mounting adapters are made from 300 series stainless steel.







**Table 1: Standard Studs**

| Part Number | Size             | Illustration  |
|-------------|------------------|---|
| 04365657    | 3/8-24 to 3/8-24 |  |
| 87055-01    | 3/8-24 to M6X1   |  |
| 87910-01    | 3/8-24 to 1/2-20 |  |
| 87931-01    | M6X1 to M6X1     |  |
| 89139-01    | 3/8-24 to 1/4-28 |  |

**Table 2: Adhesive Studs**




| Part Number | Size   | Illustration  |
|-------------|--------|---|
| 04284020    | 3/8-24 |  |

**Table 3: 1-3/8 Hex Plate Studs**

| Part Number | Size                     | Illustration  |
|-------------|--------------------------|---|
| 107754-01   | 3/8-24 UNF to 1/4 NPT    |  |
| 107755-01   | 3/8-24 UNF to 1/2-20 UNF |  |
| 107756-01   | 3/8-24 to 3/8-24         |  |
| 197757-01   | M6X1 to M6X1             |  |
| 125094-01   | 3/8-24 UNF to M8X1       |  |
| 128038-01   | 3/8-24 UNF to 1/4-28 UNF |  |



**Table 4: Quick Disconnect Studs**

| Part Number | Description                       | Illustration  |
|-------------|-----------------------------------|---|
| 43055-01    | Union Mounting Base Nut           |  |
| 128689-01   | Quick Disconnect Stud Base        |  |
| 128690-01   | Quick Disconnect Transducer Piece |  |

Graphs




Figure 2: Typical Phase Response






Figure 3: Typical Amplitude Response



1. Velocity axis (mm/s peak-peak)
2. Displacement axis (mm peak-peak)
3. Acceleration axis (m/s<sup>2</sup> peak-peak)

**Figure 4: Operating Range for Metric Units**



1. Velocity axis (in./s peak-peak)
2. Displacement axis (in. peak-peak)
3. Acceleration axis (g peak-peak)

**Figure 5: Operating Range for English Units**




Figure 6: Typical Low Frequency Noise Floor

© 2000-2017 Bently Nevada, Inc. All rights reserved.

\* Denotes a trademark of Bently Nevada, Inc., a wholly owned subsidiary of General Electric Company.

Teflon™ is a trademark of The Chemours Company.

The information contained in this document is subject to change without prior notice.

Printed in USA. Uncontrolled when transmitted electronically.

1631 Bently Parkway South, Minden, Nevada USA 89423

Phone: 775.782.3611 Fax: 775.215.2873

<http://www.GEmeasurement.com>